

EX42011 Series

Industrial 10/100BASE-TX to 100BASE-FX Media Converter



Value

- > 1-port 10/100BASE-TX and 1-port 100BASE-FX
- > 12 to 48VDC Power inputs
- > -10°C to 60°C (14°F to 140°F) operating temperature range
- > Provides DIN-Rail mounting
- > Full wire-speed forwarding rate

Features

- > Provides 1-port 10/100BASE-TX plus 1-port 100BASE-FX
- > The fiber port is available with SC or ST with a fiber connection that can reach up to 120Km (74.4miles)
- > -10°C to 60°C (-14°F to 140°F) and is tested for functional operation @ -20°C to 70°C (-4°F to 158°F)
- > 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- > Supports 12 to 48VDC Power inputs
- > Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment
- > 384K bits buffer memory

Ordering Information

EX42011-XY-I-P Industrial 10/100BASE-TX to 100BASE-FX Media Converter

100FX Fiber Options :

- (XY) = 1A : Multi Mode (SC) - 2Km (1310nm)
 1B : Multi Mode (ST) - 2Km (1310nm)
 2A : Single Mode (SC) - 20Km (1310nm)
 2B : Single Mode (SC) - 40Km (1310nm)
 2D : Single Mode (ST) - 20Km (1310nm)
 1H : Multi Mode (SC) WDM -TX: 1310nm/RX:1550nm - 2Km
 1J : Multi Mode (SC) WDM -TX: 1310nm/RX:1550nm - 5Km
 2E : Single Mode (SC) WDM -TX:1310nm/RX:1550nm - 20Km
 2F : Single Mode (SC) WDM -TX:1310nm/RX:1550nm - 40Km
 1I : Multi Mode (SC) WDM -TX: 1550nm/RX:1310nm - 2Km
 1K : Multi Mode (SC) WDM -TX: 1550nm/RX:1310nm - 5Km
 2G : Single Mode (SC) WDM -TX:1550nm/RX:1310nm - 20Km
 2H : Single Mode (SC) WDM -TX:1550nm/RX:1310nm - 40Km
 *More 100FX Fiber options available upon request

Installation Type :

- (I) = 1 : DIN-Rail (mounting kit is included)

Power Connector Options :

- (P) = A : Terminal Block*

*Option A - The Terminal Block type external power supplies are not included. Please order the following part numbers:

DR-30-24, DR-60-24, DR-75-24, DR-120-24 or 41-136046-X (X)=1: US, 2: EU, 3: UK, 4: AU, 5: JP

Specifications

Technology	
Standards	<ul style="list-style-type: none"> IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX/100BASE-FX, IEEE802.3x
Forward and Filtering Rate	<ul style="list-style-type: none"> 14,880pps for 10Mbps 148,810pps for 100Mbps
Packet Buffer Memory	<ul style="list-style-type: none"> 384K bits
Processing Type	<ul style="list-style-type: none"> Store-and-Forward Half-duplex back-pressure and IEEE802.3x full-duplex flow control

Power	
Input	<ul style="list-style-type: none"> Input Voltage: 12 to 48VDC (Terminal Block)
Power Consumption	<ul style="list-style-type: none"> 4.3W Max. 0.3A @ 12VDC, 0.15A @ 24VDC, 0.07A @ 48VDC
Reverse Polarity Protection	<ul style="list-style-type: none"> Present

Mechanical	
Casing	<ul style="list-style-type: none"> Plastic case IP30
Dimensions	<ul style="list-style-type: none"> 26mm (W) x 70mm (D) x 110mm (H) (1.02" (W) x 2.76" (D) x 4.33" (H))
Weight	<ul style="list-style-type: none"> 0.2Kg (0.44lb.)
Installation	<ul style="list-style-type: none"> DIN-Rail (Top hat type 35mm) Mounting

Interface	
Ethernet Port	<ul style="list-style-type: none"> 10/100BASE-TX: 1 port 100BASE-FX: 1 port
LED Indicators	<ul style="list-style-type: none"> Per Unit: Power Status (Power1) Per Port: 10/100TX, 100FX: Link/Activity (Green), Speed (Yellow)

Environment	
Operating Temperature	<ul style="list-style-type: none"> -10°C to 60°C (14°F to 140°F) Test @ -20°C to 70°C (-4°F to 158°F)
Storage Temperature	<ul style="list-style-type: none"> -25°C to 85°C (-13°F to 185°F)
Ambient Relative Humidity	<ul style="list-style-type: none"> 5% to 95% (non-condensing)

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> Manufactured in an ISO9001 facility
Safety	<ul style="list-style-type: none"> UL60950-1, EN60950-1, IEC60950-1
EMI	<ul style="list-style-type: none"> FCC Part 15, Class A, VCCI EN61000-6-4 <ul style="list-style-type: none"> EN55022 EN61000-3-2 EN61000-3-3
EMS	<ul style="list-style-type: none"> EN61000-6-2 <ul style="list-style-type: none"> EN61000-4-2 (ESD Standards) <ul style="list-style-type: none"> Contact: + / - 6KV Air: + / - 8KV EN61000-4-3 (Radiated RFI Standards) <ul style="list-style-type: none"> 10V/m, 80 to 1000MHz; 80% AM 3V/m, 1400 to 2000MHz; 80% AM 1V/m, 2000 to 3000MHz; 80% AM EN61000-4-4 (Burst Standards) <ul style="list-style-type: none"> Signal Ports: + / - 4.4KV D.C. Power Ports: + / - 4.4KV EN61000-4-5 (Surge Standards) <ul style="list-style-type: none"> Signal Ports: + / - 1KV; Line-to-Line D.C. Power Ports: + / - 0.5KV; Line-to-earth EN61000-4-6 (Induced RFI Standards) <ul style="list-style-type: none"> Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM EN61000-4-8 (Magnetic Field Standards) <ul style="list-style-type: none"> 30A/m @ 50, 60Hz
Environmental Test Compliance	<ul style="list-style-type: none"> IEC60068-2-6 Fc (Vibration Resistance) <ul style="list-style-type: none"> 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport) IEC60068-2-27 Ea (Shock) <ul style="list-style-type: none"> 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport) FED STD 101C Method 5007.1 (Free fall w/ package) <ul style="list-style-type: none"> -Tested with Cross Weight and Drop High standard table

Diagrams

Unit: mm

