

# EMC1600 Series

株式会社 サイバネット

## 16-Bay Media Converter and Ethernet Extender Chassis

### ✓ Value



- › Redundant power supplies with Ideal Central Point, powered up to 16 Media Converters and Ethernet Extenders
- › The chassis system is capable of hot-swap installation of Media Converters, Ethernet Extenders and redundant power supply

## Features

- › House up to sixteen Media Converters (EL2321, EL2211, EL2315, EM1100/EM2100, EM1000/EM2000, EM1000S/EM2000S, EM120, EL100/EL200, and EL110/EL210 series) and Ethernet Extenders (ED3101 and ED3331)
- › Non-stop operation and minimal downtime
- › Hot-swappable: Media Converters, Ethernet Extenders and redundant power supply modules
- › Redundant 100 - 240VAC 50 - 60Hz Internal Universal PSU or 48VDC Power inputs
- › Power redundancy: The other redundant power supply module is capable of taking over immediately if one of the power supply modules fails
- › Load sharing: Two internal power supply modules provided for load sharing purposes
- › Power isolation: Media Converter and Ethernet Extender bay power isolation ensures each bay is electrically isolated from each other
- › Over current protection: Fuse on PCBA for each Media Converter and Ethernet Extender bay and power supply module
- › 0°C to 45°C (32°F to 113°F) operating temperature range
- › Metal case, standard 19" rack-mount size, two-unit-height
- › Supports Rack Mounting installation

## Ordering Information

EMC1600	16-Bay Media Converter and Ethernet Extender Chassis, includes 2 AC Power Supplies (EMC1600-RPSA)
EMC1600-RPSA	Redundant AC Power Supply (84W) for EMC1600
EMC1600-RPSA2	Redundant AC Power Supply (108W) for EMC1600
EMC1600-RPSD	Redundant DC 48V Power Supply (65W) for EMC1600

### NOTES :

\* The optional Media Converter and Ethernet Extender series for EMC1600 are to be separately ordered by customers' choice

\* The following is the list of the Media Converter series:

EL2321, EL2211, EL2315, EM1100/EM2100, EM1000/EM2000, EM1000S/EM2000S, EM120, EM120, EL100/EL200, EL110/EL210 series

\* The following is the list of the Ethernet Extender series:

ED3101 and ED3331

# Specifications

株式会社 サイバネテック

Power	
Input	<ul style="list-style-type: none"> <li>• 100 - 240VAC, 50 - 60Hz Internal Universal PSU</li> <li>• + / - 48VDC</li> </ul>
Power Consumption	<ul style="list-style-type: none"> <li>• System: 5.4W Max.</li> </ul>

Mechanical	
Casing	<ul style="list-style-type: none"> <li>• Metal case</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>• 440mm (W) x 276mm (D) x 90mm (H) (17.32" (W) x 10.87" (D) x 3.54" (H))</li> <li>• Standard 19" rack-mount size, two-unit-height</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 6.8Kg (14.96lbs.)</li> </ul>
Installation	<ul style="list-style-type: none"> <li>• Rack Mounting</li> </ul>

Interface	
LED Indicators	<ul style="list-style-type: none"> <li>• Per Unit: Power Status (Power)</li> </ul>

Environment	
Operating Temperature	<ul style="list-style-type: none"> <li>• 0°C to 45°C (32°F to 113°F)</li> </ul>
Storage Temperature	<ul style="list-style-type: none"> <li>• -10°C to 70°C (14°F to 158°F)</li> </ul>
Ambient Relative Humidity	<ul style="list-style-type: none"> <li>• 5% to 95% (non-condensing)</li> </ul>

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> <li>• Manufactured in an ISO9001 facility</li> </ul>
Safety	<ul style="list-style-type: none"> <li>• UL60950-1</li> </ul>
Emission Compliance	<ul style="list-style-type: none"> <li>• CE Mark Class A</li> <li>• FCC Part 15 Class A</li> </ul>

# Diagrams

Unit: mm

